

# **Technical Data**

# Tar Prime

### **DESCRIPTION:**

GemSeal® Tar Prime is a unique ready to use, job-proven primer formulation of acrylic polymers that allows sealer materials to bond effectively and dry quickly.

#### **USES:**

Prevents oil and grease spots from "bleeding" through fresh blacktop sealer. Also for priming of grease, oil and gasoline concentration on asphaltic concrete surfaces before application of sealcoat materials.

#### **APPLICATION:**

- 1. Clean spots thoroughly with water.
- 2. Scrape heavy spots and remove loose materials. Particularly resistant spots may need cleaning with a strong detergent or driveway cleaner.
- 3. Stir Tar Prime until throughly mixed.
- 4. Apply to area with clean brush, broom or spray. Do not dilute.
- 5. Allow to dry to touch before applying sealer over primer (usually two hours or less).

# WEATHER CONDITIONS:

Apply only when air and ground temperature is 50°F and rising. Do not apply if rain is expected within four hours.

#### **CLEAN-UP:**

Clean application tools at once with soap and water.

# **COVERAGE:**

Coverage varies between 250 and 300 square feet per gallon depending upon surface texture and porosity of area coated.

# **PACKAGING:**

Available in 5 gallon pails.

# **STORAGE:**

Keep from freezing. Do not store in direct sunlight. Do not store where temperature exceeds 100°F.

#### **SERVICE:**

Timely service is available within a 300 mile radius of our manufacturing facilities.

#### **ATTENTION:**

GemSeal® Tar Prime should be protected from freezing.

#### **CAUTION:**

May cause an allergic skin reaction. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

**WARNING:** This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Thirty-seven percent of the mixture consists of ingredient(s) of unknown acute toxicity.



# MANUFACTURING & CUSTOMER SERVICE: Call (866) 264-8273 to find the nearest GemSeal location to purchase Tar Prime.

GemSeal Pavement Products Corporate Headquarters: 3700 Arco Corporate Drive, Suite 425 Charlotte, NC 28273

GemSeal Pavement Products warrants that for a period of one (1) year from date of purchase this product shall be free from manufacturing defects and shall meet or exceed performance standards listed in the technical data sheet for the product at the time of sale, if used as directed and within the stated shelf life. This Limited Warranty applies only if the product is stored, used, and applied over a properly prepared substrate in strict accordance with applicable specifications and instructions issued by GemSeal Pavement Products. The Limited Warranty will not apply if the product is altered, modified, or misused after it has left the control of GemSeal Pavement Products. GemSeal Pavement Products will not be responsible for defects caused by factors beyond its control, including but not limited to workmanship, application equipment, weather, acts of God, structural failure, condition or movement of substrate, improper additives, poor drainage, ponded water, improper maintenance, damage from snow removal equipment, and normal wear and tear. GemSeal Pavement Products does not warrant that the product or any method of use or application would be suitable for any particular site conditions.

All warranty claims must be submitted in writing, with proof of purchase, to the following address: 3700 Arco Corporate Drive, Suite 425, Charlotte, NC 28273. Unused portions of product must be returned upon request. Replacement of defective product or, at GemSeal Pavement Products' option, refund of the purchase price of defective product shall be the buyer's sole remedy under this Limited Warranty. In no event shall GemSeal Pavement Products be liable for any damages in excess of the purchase price of the defective product. This Limited Warranty does not cover labor costs for product application, replacement, or repair. GEMSEAL PAVEMENT PRODUCTS SHALL IN NO EVENT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES, INCLUDING BUT NOT LIMITED TO DAMAGES FOR LOST SALES OR PROFITS, BUSINESS INTERRUPTION, DELAYS, PHYSICAL DAMAGE TO OTHER MATERIALS OR PROPERTY, OR LOSS OF USE OF PROPERTY.

THIS LIMITED WARRANTY IS PROVIDED IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. GEMSEAL PAVEMENT PRODUCTS EXPRESSLY DISCLAIMS ANY OTHER WARRANTIES, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification or extension of this Limited Warranty shall be valid unless given in writing and signed by an authorized officer of GemSeal Pavement Products. Sales personnel and product distributors are not authorized to modify or extend this Limited Warranty.