



## TARLOC® MPC PRIMER for Coal Tar Emulsion Sealer

### DESCRIPTION:

Tarloc® MPC Primer is a pavement primer for oxidized, worn difficult to clean surfaces to improve bonding and wear of coal tar emulsion sealcoats.

### FEATURES:

- Primer for badly oxidized asphalt pavements prior to sealing
- Primer for hard to clean areas, and polished aggregate conditions.
- Primer for concrete pavements prior to sealing.
- Oil spot sealer on both asphalt and concrete.
- Black-out paint for traffic/parking lines, etc.

### APPLICATION:

Tarloc® MPC can be applied by brush, squeegee, line paint sprayer or bulk truck spray-bar/hand wand. Since mild settling is possible, the product should be thoroughly stirred before application to the pavement. Stir to a uniform consistency. Apply Tarloc MPC in a thin film. Avoid over application. A wearing coat (s) of Latex modified sealer is then recommended over the Tarloc MPC Primer.

### APPLICATION RATE:

.025 to .050 gal./sq. yd.

### For Asphalt Surfaces:

Mix 1 part Tarloc MPC with 1 part water.

### For Concrete Surfaces:

Mix 1 part Tarloc MPC to 2 parts water.

### PHYSICAL PROPERTIES:

APPEARANCE Viscous, grey-green liquid

SOLIDS 30%

VISCOSITY 2,000 cPs

DENSITY 9.0 Lb./Gal.

ODOR Coal Tar

DRIED FILM COLOR Black

DRYING TIME 10 to 30 minutes (depending on surface conditions and thickness of application).

### PACKAGING:

Available in 5 gallon pails.

### STORAGE:

Store in a cool, dry area. Avoid freezing. Product is no longer useful after freezing.

### SPECIAL HANDLING:

Tarloc® MPC is slightly more irritable to the skin than regular pavement sealer. Protective clothing and skin creams should be used at all times.

### CAUTION:

Contains coal tar, a skin irritant. Keep out of reach of children. Do not take internally. Avoid prolonged or repeated contact with skin or breathing of vapors. In case of contact with eyes, flush with plenty of water, and seek immediate medical attention. Use with adequate ventilation. Do not use in confined areas.

Tarloc® is the registered trademark of Southern Emulsions, Inc.



## Tarloc MPC Primer

### **MANUFACTURING & CUSTOMER SERVICE:**

**Call (866) 264-8273 to find the nearest GemSeal location to purchase Tarloc MPC Primer.**

GemSeal Pavement Products  
Corporate Headquarters:  
3700 Arco Corporate Drive, Suite 425  
Charlotte, NC 28273

GemSeal Pavement Products warrants that for a period of one (1) year from date of purchase this product shall be free from manufacturing defects and shall meet or exceed performance standards listed in the technical data sheet for the product at the time of sale, if used as directed and within the stated shelf life. This Limited Warranty applies only if the product is stored, used, and applied over a properly prepared substrate in strict accordance with applicable specifications and instructions issued by GemSeal Pavement Products. The Limited Warranty will not apply if the product is altered, modified, or misused after it has left the control of GemSeal Pavement Products. GemSeal Pavement Products will not be responsible for defects caused by factors beyond its control, including but not limited to workmanship, application equipment, weather, acts of God, structural failure, condition or movement of substrate, improper additives, poor drainage, ponded water, improper maintenance, damage from snow removal equipment, and normal wear and tear. GemSeal Pavement Products does not warrant that the product or any method of use or application would be suitable for any particular site conditions.

All warranty claims must be submitted in writing, with proof of purchase, to the following address: 3700 Arco Corporate Drive, Suite 425, Charlotte, NC 28273. Unused portions of product must be returned upon request. Replacement of defective product or, at GemSeal Pavement Products' option, refund of the purchase price of defective product shall be the buyer's sole remedy under this Limited Warranty. In no event shall GemSeal Pavement Products be liable for any damages in excess of the purchase price of the defective product. This Limited Warranty does not cover labor costs for product application, replacement, or repair. GEMSEAL PAVEMENT PRODUCTS SHALL IN NO EVENT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES, INCLUDING BUT NOT LIMITED TO DAMAGES FOR LOST SALES OR PROFITS, BUSINESS INTERRUPTION, DELAYS, PHYSICAL DAMAGE TO OTHER MATERIALS OR PROPERTY, OR LOSS OF USE OF PROPERTY.

THIS LIMITED WARRANTY IS PROVIDED IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. GEMSEAL PAVEMENT PRODUCTS EXPRESSLY DISCLAIMS ANY OTHER WARRANTIES, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification or extension of this Limited Warranty shall be valid unless given in writing and signed by an authorized officer of GemSeal Pavement Products. Sales personnel and product distributors are not authorized to modify or extend this Limited Warranty.