



Ultra

DESCRIPTION:

GemSeal® Ultra latex is an additive used with coal tar emulsion sealcoats to provide a tougher protective sealing film. Ultra should be used in all formulations containing sand to prevent aggregate rollout and increase life of film. Ultra Latex complies with all FAA specifications and ASTM specifications for coal tar sealcoats. Ultra latex additive is a milky blue latex containing proprietary surfacants and modifiers with a minimum solids content of 40%.

FEATURES:

- Superior adhesion, crack resistance, fast setup and proper sand suspension
- Reduces Wet Track Abrasion Resistance (ASTM D3910) loss by more than 50%
- Non flammable

APPLICATION:

The coal tar emulsion mix containing Ultra latex may be applied by conventional techniques. Allow minimum six hours drying time between coats on hot days. On cool or overcast poor drying condition days allow 24 hours between coats. Allow 24 hours curing between last coating and striping with latex paint. Consult with GemSeal recommended guidelines for complete information.

COVERAGE:

Application rates for mixes containing Ultra latex shall range from 0.10 to 0.15 gallons per square yard.

STORAGE:

Store in a cool, dry area. Avoid freezing. Product is no longer useful after freezing.

CLEAN-UP:

Use soap and water if product is still in emulsion state. Dried latex will be difficult to remove from tools and equipment. Use GemSeal hand cleaner to remove residue from hands.

INSTRUCTIONS FOR USE:

While agitating, slowly add mixing water to coal tar emulsion. Dilute Ultra latex with equal parts water and slowly add to diluted coal tar emulsion. When materials are completely mixed then slowly add the sand. Continue mixing until all ingredients are uniformly mixed.

Recommended Mix Design Limits

GemSeal Coal Tar Emulsion (RP-355e)	100 gallons
Mix water	35-45 gallons
Ultra latex	2-5 gallons
Silica sand	200-500 pounds



Ultra

CAUTION:

WARNING: This product may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Seventy-seven percent of the mixture consists of ingredient(s) of unknown acute toxicity.

MANUFACTURING & CUSTOMER SERVICE:

Call (866) 264-8273 to find the nearest GemSeal location to purchase Ultra.

GemSeal Pavement Products
Corporate Headquarters:
3700 Arco Corporate Drive, Suite 425
Charlotte, NC 28273

GemSeal Pavement Products warrants that for a period of one (1) year from date of purchase this product shall be free from manufacturing defects and shall meet or exceed performance standards listed in the technical data sheet for the product at the time of sale, if used as directed and within the stated shelf life. This Limited Warranty applies only if the product is stored, used, and applied over a properly prepared substrate in strict accordance with applicable specifications and instructions issued by GemSeal Pavement Products. The Limited Warranty will not apply if the product is altered, modified, or misused after it has left the control of GemSeal Pavement Products. GemSeal Pavement Products will not be responsible for defects caused by factors beyond its control, including but not limited to workmanship, application equipment, weather, acts of God, structural failure, condition or movement of substrate, improper additives, poor drainage, ponded water, improper maintenance, damage from snow removal equipment, and normal wear and tear. GemSeal Pavement Products does not warrant that the product or any method of use or application would be suitable for any particular site conditions.

All warranty claims must be submitted in writing, with proof of purchase, to the following address: 3700 Arco Corporate Drive, Suite 425, Charlotte, NC 28273. Unused portions of product must be returned upon request. Replacement of defective product or, at GemSeal Pavement Products' option, refund of the purchase price of defective product shall be the buyer's sole remedy under this Limited Warranty. In no event shall GemSeal Pavement Products be liable for any damages in excess of the purchase price of the defective product. This Limited Warranty does not cover labor costs for product application, replacement, or repair. GEMSEAL PAVEMENT PRODUCTS SHALL IN NO EVENT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES, INCLUDING BUT NOT LIMITED TO DAMAGES FOR LOST SALES OR PROFITS, BUSINESS INTERRUPTION, DELAYS, PHYSICAL DAMAGE TO OTHER MATERIALS OR PROPERTY, OR LOSS OF USE OF PROPERTY.

THIS LIMITED WARRANTY IS PROVIDED IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. GEMSEAL PAVEMENT PRODUCTS EXPRESSLY DISCLAIMS ANY OTHER WARRANTIES, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification or extension of this Limited Warranty shall be valid unless given in writing and signed by an authorized officer of GemSeal Pavement Products. Sales personnel and product distributors are not authorized to modify or extend this Limited Warranty.