



# GemSeal Black Diamond XL Sealer

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 10/26/2016

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : GemSeal Black Diamond XL Sealer  
Product code : Not available

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Asphalt Sealant

#### 1.3. Details of the supplier of the safety data sheet

GemSeal Pavement Products  
3700 Arco Corporate Drive, Suite 425  
Charlotte, NC 28273 - USA  
T 866-264-8273 Tech Service: Monday - Friday; 8:00am - 5:00pm EST

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300  
: INTERNATIONAL +01-703-527-3887

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin irritation 2

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Hazard statements (GHS-US) : May cause an allergic skin reaction. May cause genetic defects. May cause cancer.  
Precautionary statements (GHS-US) : Wash hands thoroughly after handling. Wear protective gloves. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS-US)

2% of the mixture consists of ingredient(s) of unknown acute toxicity.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Residues, petroleum, steam-cracked	(CAS No) 64742-90-1	15 - 30	Flam. Liq 4 Skin Irrit. 2
Quartz	(CAS No) 14808-60-7	5 - 10	Acute Tox. 4 (Oral)
Mica	(CAS No) 12001-26-2	3 - 7	Not classified
Aluminum silicate	(CAS No) 1327-36-2	1 - 5	Skin Irrit. 2 Eye Irrit. 2A
Feldspar	(CAS No) 68476-25-5	1 - 5	Eye Irrit. 2A STOT SE 3
Titanium dioxide	(CAS No) 13463-67-7	0.1 - 1	Not classified

# GemSeal Black Diamond XL Sealer

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Name	Product identifier	%	GHS-US classification
Benzo(a)pyrene	(CAS No) 50-32-8	< 0.1	Skin Sens. 1 Muta. 1B Carc. 1A Repr. 1B
Naphthalene	(CAS No) 91-20-3	< 0.1	Acute Tox. 4 (Oral) Carc. 2

\* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/injuries after ingestion : May cause stomach distress, nausea or vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Treat for surrounding material.
- Unsuitable extinguishing media : None known.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : May include, and are not limited to: oxides of carbon.

#### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### 6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container.

#### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing vapour or mist. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed.

# GemSeal Black Diamond XL Sealer

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>Residues, petroleum, steam-cracked (64742-90-1)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	Not applicable.
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	Not applicable.
<b>Quartz (14808-60-7)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	((10 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (resp)); ((30 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (total)); ((250)/(%SiO <sub>2</sub> +5) mppcf TWA (resp))
<b>Mica (12001-26-2)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	20 mppcf (respirable dust)
<b>Aluminum silicate (1327-36-2)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	Not applicable.
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	Not applicable.
<b>Feldspar (68476-25-5)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	Not applicable.
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	Not applicable.
<b>Titanium dioxide (13463-67-7)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
<b>Benzo(a)pyrene (50-32-8)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	Not applicable.
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
<b>Naphthalene (91-20-3)</b>		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm

### 8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear suitable gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Appearance	: Low to moderate viscosity creamy liquid
Colour	: Dark brown to dark gray / black

# GemSeal Black Diamond XL Sealer

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Odour	: Aromatic.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butyl acetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: No data available.
Self-ignition temperature	: Product is not self-igniting.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density (water = 1)	: 1.08 – 1.20.
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, cPs	: 1,500 – 6,500 cPs.
Explosive properties	: No data available.
Oxidizing properties	: No data available.
Explosive limits	: Product is not explosive. However, formation of explosive air/steam mixtures is possible.

### 9.2. Other information

VOC content : No data available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2. Chemical stability

Stable under normal storage conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

### 10.4. Conditions to avoid

Heat. Incompatible materials.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

GemSeal Black Diamond XL Sealer	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	Not available
Residues, petroleum, steam-cracked (64742-90-1)	
LD50 oral rat	4320 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
Quartz (14808-60-7)	
LD50 oral rat	500 mg/kg

# GemSeal Black Diamond XL Sealer

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

<b>Titanium dioxide (13463-67-7)</b>	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg

<b>Naphthalene (91-20-3)</b>	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	>20 g/kg
LC50 inhalation rat	> 340 mg/m <sup>3</sup> /1h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Based on available data, the classification criteria are not met.  
Respiratory or skin sensitization : Based on available data, the classification criteria are not met.  
Germ cell mutagenicity : Based on available data, the classification criteria are not met.  
Carcinogenicity : Based on available data, the classification criteria are not met.

<b>Quartz (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans (airborne particles of respirable size)
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens

<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans (airborne, unbound particles of respirable size)

<b>Naphthalene (91-20-3)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen

<b>Benzo(a)pyrene (50-32-8)</b>	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Based on available data, the classification criteria are not met.  
Specific target organ toxicity (single exposure) : Based on available data, the classification criteria are not met.  
Specific target organ toxicity (repeated exposure) : Based on available data, the classification criteria are not met.  
Aspiration hazard : Based on available data, the classification criteria are not met.  
Symptoms/injuries after inhalation : May cause respiratory irritation.  
Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.  
Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.  
Symptoms/injuries after ingestion : May cause stomach distress, nausea or vomiting.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

### 12.2. Persistence and degradability

<b>GemSeal Black Diamond XL Sealer</b>	
Persistence and degradability	No additional information available.

### 12.3. Bio accumulative potential

<b>GemSeal Black Diamond XL Sealer</b>	
Bio-accumulative potential	No additional information available.

### 12.4. Mobility in soil

<b>GemSeal Black Diamond XL Sealer</b>	
Ecology - soil	No additional information available.

### 12.5. Other adverse effects

Other adverse effects : No additional information available.  
Effect on ozone layer : No additional information available

# GemSeal Black Diamond XL Sealer

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Effect on the global warming : No known ecological damage caused by this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

No additional information available

### SECTION 14: Transport information

In accordance with DOT

#### 14.1. UN number

Not applicable

#### 14.2. UN proper shipping name

Not applicable

#### 14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Mica	CAS No 12001-26-2
------	-------------------

#### Naphthalene (91-20-3)

Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

SARA Section 313 - Emission Reporting 0.1 %

#### Benzo(a)pyrene (50-32-8)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 0.1 %

#### 15.2. US State regulations

#### GemSeal Black Diamond XL Sealer

State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	---

### SECTION 16: Other information

Indication of changes : None.

Date of issue : 10/26/2016

Data sources : SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*