



CERTIFICATE OF COMPLIANCE

FOR MATERIAL SUPPLIED BY
RIGHT POINTE COMPANY

DATE: September 30, 2016
ISSUED TO: Gem Seal Products
PRODUCT NAME: # 3405 Regular
SPECIFICATIONS: OK DOT Spec. 701.08(d); ASTM D 6690 Type I & II; AASHTO M 324
BUY AMERICA: *This product is manufactured in the United States of America.*

3405 Regular as manufactured by Right Pointe Company meets and will continue to meet the requirements of, OK DOT Specification 701.08(d), ASTM D 6690 Type II, SS-S-1401 & AASHTO M 324.

TEST PARAMETER	METHOD	SPECIFICATIONS	RESULTS
Penetration at 77 °F, 0.1 mm	ASTM D 5329	90 max.	PASS
Resilience, %	ASTM D 5329	60% min	PASS
Flow at 140 °F, mm	ASTM D 5329	3 mm max	PASS
Bond (-20 °F/100% Ext.)	ASTM D 5329	PASS	PASS
Asphalt Compatibility	ASTM D 5329	PASS	PASS
Softening point, °F	ASTM D 36	176 °F min.	PASS
Mandrel Bend (-19°F, 1 inch)	ASTM D 522	No Cracking	PASS

Samples pulled from job-site inventories may exhibit varying results from the above due to weather, shipping and handling conditions beyond our control.

Such material complies with the Oklahoma Department of Transportation Standard Specification 701.08(e) for hot poured joint sealer.

Sincerely,

Right Pointe Company

Philippe Gauthier
Technical Director

Right Pointe Company
234 Harvestore Drive
DeKalb, IL 60115

Phone: 888.755.5700
Office: 815.754.5700
Fax: 815.754.5702