



Stress-free boom rotates around hose.



Electric heated wand option.



Optional heated draw-off option.



Optional engine cover.



Optional rotary screw air compressor.



Simple seal controller.

SPECIFICATIONS

	M1**	M2**	M4
Material Capacity gal. (liters)	150 (568)	230 (871)	410 (1552)
Engine HP	25 Diesel 40 Compressor Model	25 Diesel 40 Compressor Model	25 Diesel 40 Compressor Model
Heating Method	Diesel	Diesel	Diesel
Heat Rating BTUs	250,000	290,000	400,000
Material Pump GPM (LPM)	20 (76)	20 (76)	20 (76)
GVWR lbs. (kg)	5200 (2359)	6840 (3103)	9520 (4318)
GAWR lbs. (kg)	7000 (3175)	7000 (3175)	10,000 (4536)
Axles/ Suspension	1 (torsion type)	2 (torsion type)	2 (torsion type)
Brake Type	Electric*	Electric*	Electric*
Loading Height in. (mm)	50 (1270)	48 (1219)	54 (1372)
Loading Doors	Single Curbside	Dual	Dual
Fuel Capacity gal. (liters)	33 (125)	33 (125)	33 (125)
Hydraulic Capacity gal. (liters)	33 (125)	33 (125)	33 (125)
Heat Transfer Oil gal. (liters)	22 (83)	30 (114)	40 (151)
Dimensions L x W x H in. (L x W x H mm.)	152 x 82 x 93 (3692 x 2083 x 2362)	170 x 79 x 92 (4318 x 2007 x 2336)	185 x 90 x 90 (4699 x 2286 x 2286)
Shipping Weight lbs. (kg)	4,200 (1,905)	4,750 (2,155)	6,000 (2,721)
Warranty	One Year Bumper to Bumper		

Due to continuous improvement, specifications are subject to change without notice.

* Available with surge brakes.

** Available without pump.



Lean more at cimlinepmg.com

Phone : 800-328-3874 Email : info@cimline.com



**INNOVATION
IN PRESERVATION**

M-Series



STANDARD




LED Lighting



Lowest Height
Largest Door



Torsion Axles



Performance Tank Design

The reputation of the MAGMA for simple, safe, sustainable operation lives on with the M-Series which marks a new chapter for Cimline™ with signature safety green paint. Going green means more than a paint color change as the M-Series comes standard with lower emissions, lower fuel consumption and quieter operation for a better work environment. M-Series's most popular features of the low-profile design, high production and easy to use operator features continue to make Cimline™ the leader in crack sealing.

Ergonomic Simplicity: M-Series offers the highest levels of operator comfort with a completely redesigned delivery system. The no-stress boom swivels around the heated sealing hose, unlike any other machine, minimizing hose stress and providing the industry-leading operating range. Add the new heated wand option for even better comfort and ease of use.

Community and Operation Friendly: The clean Tier IV compliant diesel engine runs at lowest possible RPM for the best combination of performance and fuel economy. The standard noise abatement muffler, when combined with the engine cover option, reduces noise levels up to 40% when compared to other models.

M-SERIES FAMILY



M1
without pump



M2
with pump



M1
with pump



M4 dual hose, dual pump and conveyor