

RediMat™

the original flexible surface applied mat

The original surface applied RediMat detectable warning is constructed of extremely durable, UV protected polyurethane. This flexible mat has a proprietary pre-applied adhesive system that enables installation in less than 10 minutes, drastically reducing labor time and expense, but not at the cost of durability.



Features

- **No adhesives to apply** – simply remove protective backing, exclusive peel & stick technology
- **Installs on both asphalt and concrete** – multi-surface adhesive system
- **Conforms to uneven surfaces** – flexible polyurethane material
- **Unbreakable** – will not chip, crack, or splinter
- **Radius Ready** – Available in “Wedge” shape
- **Beveled Edge** – For easy pedestrian access
- **RediMatWZ™** – For temporary work zone applications, reusable, and safety orange color
- Includes stainless steel anchors to meet DOT requirements



Installation



Easiest installation of any surface applied detectable warning. Just peel and stick, roll the mat to ensure a secure bond and install stainless steel anchors. Less than 10 minutes - start to finish.

Physical Characteristics

- **Hardness** - 90 (Shore A)
- **Stain Resistance** - No Significant Change
- **Dome Spacing** - Inline, 2.35”
- **Slip Resistance** - .90
- **Taber Abrasion** - (1000gms/1000 cycles) 150mgs
- **Color** - Integral Throughout

Colors



Safety Yellow



Brick Red




Black


Sizes




2' x 2'
*




2' x 3'




2' x 4'



2' x 5'



3' x 2.5'



3' x 4'



Wedge

10 ft
radius

*Special order only